

# EARTHMOVING RADIAL

**M4AT**


only 16.00R25


 PROTECTED AREA WITH 200% TREAD DEPTH LEVEL  
 GESCHÜTZTE FLÄCHE DURCH 150% PROFILTIEFE

 REINFORCED SIDEWALLS FOR HIGH CUT RESISTANCE  
 VERSTÄRKTE SEITENWAND, HOHER SCHUTZ GEGEN SCHNITTE

 TRACTION LUG  
 PROFILRILLEN


ECOMEGA M4AT has been designed for rigid and articulated dumper applications. The deep tread assures an exceptional tread wear. The non-directional tread design provides good fore and aft traction. Excellent lateral and side traction performance. The strong and reinforced sidewalls resist cuts and snags. Best traction in the most severe operating conditions. Special compound for a longer tyre life, cut and heat resistance compound available on request. Improved square shoulder for a larger footprint on the ground.

ECOMEGA M4AT ist konzipiert für Muldenkipper-Einsätze. Das tiefe Profil sorgt für niedrigen Reifenverschleiß. Das nicht lafrichtungsgebundene Profil garantiert hervorragenden Fahrkomfort und beste Traktion. Verstärkte schnitt- und stoßresistente Flanken bürgen dank spezieller Gummimischungen für Höchstleistungen unter härtesten Arbeitsbedingungen. Außerdem garantieren sie höhere Hitzebeständigkeit auf langen Strecken und die kantigen Schultern verbessern die Bodenhaftung.

SIZE	RIM	P.R. or S.R.	TRA	T.D. (mm)	S.W. (mm)	O.D. (mm)	L.I. / S.S.	TT/TL
16.00R25	11.25 - 25/2.0	2 **	E4	45	432	1.548	177 B	TL
23.5R25	19.50 - 25/2.5	2 **	E4	47	597	1.673	185 B	TL
26.5R25	22.00 - 25/3.0	2 **	E4	51	673	1.798	193 B	TL
29.5R25	25.00 - 25/3.5	2 **	E4	56	749	1.921	200 B	TL
750/65R25	24.00 - 25/3.5	2 **	E3	43	738	1.599	190 B	TL